

Product data sheet

Care oil Plus

Item no. 1012 6153 / 1012 6154 / 1012 6157 / 1012 6156 / 1013 5500 / 1012 6155

colourless, white, grey, golden brown, brown, black

Product features

Care Oil Plus with an increased content of solids, for the initial and regular treatment of heavily used natural oiled parquet by Bauwerk Parkett. Use it undiluted: do not add to mopping water. A machine is required for use.

Working with the product

Initial treatment

- The parquet surface to be treated must be clean and dry
- Shake Care Oil Plus well before use
- Apply undiluted and spread around
- Then rub the oil into the parquet surface using a single-disk machine with a white pad
- Remove/rub in any excess with a lint-free cotton cloth
- There must be no visible traces of the pad remaining

Intensive treatment

- This can be done regularly
- The procedure is identical to that of the initial treatment

Exceptions

- For heavily used surfaces of dark woods or woods stained with oil, it is preferable that the Bauwerk Care Oil Plus product of the appropriate colour is used
- This will restore the colour in scratches and abraded areas

Frequency of application

2–3 times a year, depending on how heavily the floor is used.

Safety notice

- Rags and other objects soaked in Bauwerk Care Oil Plus can self-ignite
- Please follow the instructions on the container.

Consumption: approx. 1 litre per 50 m²

Drying time

Approx. 5–6 h (Depending on room temperature and air humidity) Do not walk on the parquet surface during that period.

Storage

- Do not store at temperatures under +5 °C. Protect from heat.
- Keep away from children.

Storage life: May be stored for 1 year in well-sealed original packaging

Water hazard class: WHC 1: low water hazard

Waste code: 08 01 11