

Phtalate-free Heterogenous Luxury Vinyl Tile  
Product Standard DIN EN ISO 10582

## Specification

|           |              |                           |
|-----------|--------------|---------------------------|
| Thickness | EN ISO 24346 | 2,5 mm                    |
| Wearlayer | EN ISO 24340 | 0,55 mm                   |
| Weight    | EN ISO 23997 | ca. 4310 g/m <sup>2</sup> |

## Performance

|                         |                  |                                                                                      |
|-------------------------|------------------|--------------------------------------------------------------------------------------|
| Classification          | EN ISO 10874     |    |
| Fire Classification     | EN 13501-1       | B <sub>fl</sub> -s1                                                                  |
| Slip resistance         | DIN 51130        | R10                                                                                  |
| Residual Indentation    | EN ISO 24343-1   | < 0,1 mm                                                                             |
| Thermal Conductivity    | EN 12664         | 0,091 (W/m*K)                                                                        |
| Thermal Resistance      | EN 12664         | 0,028 (m <sup>2</sup> *K)/W                                                          |
| Electrostatic Behaviour | EN 1815 Method A | 0,1 kV                                                                               |
| Dimensional Stability   | EN ISO 23999     | ≤ 0,25 %                                                                             |
| Castor Chair            | EN ISO 4918      | Yes, Type W                                                                          |
| Colour Fastness         | ISO 105-B02      | > 6 Grade                                                                            |
| Sound Absorption        | EN ISO 10140-3   | approx. 3 dB                                                                         |
| Chemical Resistance     | EN ISO 26987     | Yes                                                                                  |
| Floor Heating System    |                  | Yes, max. 27° C                                                                      |
| CE Marking              | EN 14041         |  |

